



# ***PACW SERIES***

## ***AIR CURTAINS HYDRONIC TYPE***



### ***Standard Features:***

***Durable metal casing***

***Wide selection for commercial and industrial applications***

***Microprocessor control***

***Remote control handset***

***3 fan speeds (Hi, Med & Lo)***

***Reliable fan motor***

***High air throw***

***Large air volume***

***Quiet Operation***



# AIR CURTAINS (CROSS FLOW TYPE)

## STANDARD SPECIFICATIONS

## PACW SERIES

Model		PACW-1509-2L	PACW-1510-2L	PACW-1512-2L	PACW-1515-2L	PACW-1509-3L	PACW-1510-3L	PACW-1512-3L	PACW-1515-3L
Air Flow (H)	m <sup>3</sup> / h	1,610	2,240	2880	3,910	1,610	2,240	2880	3,910
Air Velocity	m / s	10	10	10	10	10	10	10	10
Air Throw	m	2.5							
Noise Level @ 1m	dB (A)	62	62	63	64	62	62	63	64
Heating Capacity	kW	7	8	9	11	8	9	14	15
Power Input	W	250	280	300	320	250	280	300	320
Power Supply	V / Ph / Hz	220 / 1 / 50							
Inlet Water Temperature	°C	70							
Outlet Water Temperature	°C	65							
Outlet Air Temperature	°C	22				24			
No. of Row in the Coil		2	2	2	2	3	3	3	3
Control		Swing-switch control / Remote Control Handset							
Dimensions	H	365	365	365	365	365	365	365	365
	W	900	1,000	1,200	1,500	900	1,000	1,200	1,500
	D	265	265	265	265	265	265	265	265
Net weight	kg	22.4	23.8	27.5	32.5	24.9	26.3	30.0	35

09 V.1.0



**Sonkor International Limited**

**Head Office**

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: [www.sonkor.com](http://www.sonkor.com)

**Branch Office, Spain**

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

**Branch Office, China**

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com