



PACC - H SERIES

**AIR CURTAINS
CROSS FLOW TYPE
WITH CERAMIC HEATER**



Efficient & Safe PTC heater
Durable metal casing
2 Fan speeds (Hi & Lo)
Operating temperature range to -18 C
Microprocessor control
- Fan & Heat modes
- Fan motor with 3 mins off delay
- Over heat protection
Remote control handset
Large air volume
Quiet Operation



AIR CURTAINS (CROSS FLOW TYPE)

STANDARD SPECIFICATIONS

PACC-H SERIES

Model		PACC-09-HS	PACC-10-HS	PACC-12-HS	PACC-15-HS	PACC-09-HX	PACC-10-HX	PACC-12-HX	PACC-15-HX
PTC CERAMIC HEATER									
Air flow	m ³ /h	912	1,040	1,280	1,670	912	1,040	1,280	1,670
Air velocity	m / s	6.5 ~ 7.5							
Air throw	m	2.3 ~ 3.0							
Noise Level @ 1m	dB (A)	64	65	67	69	64	65	67	69
Heater power	W	6,000	6,600	7,200	9,000	6,000	6,600	7,200	9,000
Motor power	W	160	200	230	300	160	200	230	300
Power supply	V / Ph / Hz	230 / 1 / 60				400 / 3 / 60			
Control		Remote Control Handset							
Dimensions	H	221	221	221	221	221	221	221	221
	W	900	1,000	1,200	1,500	900	1,000	1,200	1,500
	D	183	183	183	183	183	183	183	183
Net weight	kg	15.1	16.0	18.2	22.9	15.1	16.0	18.2	22.9

09 V.1.0



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com