



PACW2 SERIES

AIR CURTAINS HYDRONIC TYPE

**Durable metal casing
Ultra thin design
Wide selection for commercial and
industrial applications
Microprocessor control
Hi & Lo Fan speeds
High air throw
Large air volume
Quiet Operation**



AIR CURTAINS (WATER WARMING SERIES)

STANDARD SPECIFICATIONS

PACW2 SERIES

Model			PACW2 1509	PACW2 1512	PACW2 1515
Air Volume	H	m ³ / h	1,450	1,930	2,420
	L		1,050	1,400	1,750
Air Velocity	H	m / s	11		
	L		8		
Noise Level @ 1.5m	H	dB (A)	55	57	59
Power Input	H	W	230	300	330
Power Supply	V / Ph / Hz		220 - 240 / 1 / 50		
Control	Mechanical Control				
Water Velocity	Backwater temperature 100-65°C	m / s	0.49	0.65	0.82
Water Volume		kg / h	878	1170	1460
Water Resistance		Pa	2036	2715	3390
Outlet Temp.		°C	53	53	53
Quantity of heat		kW	20	28	36
Water Velocity	Backwater temperature 90-60°C	m / s	0.39	0.52	0.65
Water Volume		kg / h	698	930	1160
Water Resistance		Pa	1620	2160	2700
Outlet Temp.		°C	49	49	49
Quantity of heat		kW	16	21	27
Water Velocity	Backwater temperature 88-55°C	m / s	0.45	0.6	0.75
Water Volume		kg / h	805	1070	1330
Water Resistance		Pa	1870	2500	3115
Outlet Temp.		°C	47	47	47
Quantity of heat		kW	13	17	21
Dimensions	H	mm	352	352	352
	W		900	1,200	1,500
	D		265	265	265
Net weight	kg		27.0	34.0	40.5

09 V.1.1



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com