



INDUSTRIAL DEHUMIDIFIER

ST-300/500 SERIES

Standard Features:

***Attractive Plastic Front
For Easy Cleaning***

***Quiet Operation
And Energy Saving***

***LED display with
Humidity Setting
Within 1%***

***Washable Dust Filter, Compact
Dimensions and Continuous Drainage***

Options:

LCD Display with Timer

Hot Gas Defroster



INDUSTRIAL DEHUMIDIFIER**STANDARD SPECIFICATIONS****ST-300/500 SERIES**

Model		ST-300	ST-500
Testing standard:		30°C/80%RH	
Humidity removal:	l/24h	30	50
Power:	V/Ph/Hz	220-240/1/50	
Air flow	m ³ /h	300	350
Refrigerant:		R22/R407C	
Rated power input:	W	730	900
Rated power current:	A	3.50	4.20
Application space:	m ²	30-40	50-70
Temperature and humidity operating range	°C	5-35°C	5-35°C
	%	30-90%	30-90%
Dimensions	mm	452	452
	mm	322	322
	mm	835	835
Net weight:	Kg	28	28
Gross weight:	Kg	31	31

2009V.1.0

**Sonkor International Limited****Head Office**

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com**Branch Office, Spain**

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com