



INDUSTRIAL DEHUMIDIFIER

ST-400/600 & 700/900/1200 CSTE4 SERIES

Standard Features:

***Traditional Design With
Handle & Big Wheels
For Easy Movement***

***Quiet Operation
And Energy Saving***

***LED display with
Humidity Setting
Within 1%***

***Washable Dust Filter, Compact
Dimensions and Continuous Drainage***

Options:

LCD Display with Timer

Hot Gas Defroster

Water Pump

For ST-700/900/1200/1380/1580CSTE4



INDUSTRIAL DEHUMIDIFIER

STANDARD SPECIFICATIONS

ST-400/600 & 700/900/1200 CSTE4

Model		ST-400	ST-600	ST-700 CSTE4	ST-900 CSTE4	ST-1200 CSTE4
Testing standard:		27°C/60%RH				
Humidity removal:	Pint/24h	40	60	70	90	120
Power:	V/Ph/Hz	115/1/60				
Air flow	m ³ /h	650	650	850	850	850
Refrigerant:		R22				
Rated power input:	W	890	835	1,060	1,200	1,450
Rated power current:	A	7.8	7.3	9.3	10.5	12.6
Application space:	m ²	30-50	30-60	80-100	100-120	120-150
Temperature and humidity operating range	°C	5-35°C	5-35°C	5-35°C	5-35°C	5-35°C
	%	30-90%	30-90%	30-90%	30-90%	30-90%
Dimensions	mm	452	452	535	545	615
	mm	588	588	398	420	445
	mm	950	950	930	1,000	1,100
Net weight:	Kg	52	54	44	52	58
Gross weight:	Kg	55	56	49	55	63

2009V.1.0



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com