



INDUSTRIAL DEHUMIDIFIER

ST-400/600/800 SERIES

Standard Features:

***Modern Design with
Handle & Big Wheels
For Easy Movement***

***TOSHIBA Compressor
With Quiet Operation
And Energy Saving***

***LCD display with
Humidity Setting
And Rental Timer***

***Washable Dust Filter,
Compact Dimensions
And Continuous Drainage***

Options:

Drain Pump

Hot Gas Defroster



INDUSTRIAL DEHUMIDIFIER

STANDARD SPECIFICATIONS

ST-400/600/800 SERIES

Model		ST-400	ST-600	ST-800
Testing standard:		30°C/80%RH		
Humidity removal:	l/24h	40	60	80
Power:	V/Ph/Hz	220-240/1/50		
Air flow	m ³ /h	350	800	850
Refrigerant:		R22/R407C		
Rated power input:	W	1030	1,074	1,150
Rated power current:	A	7.8	7.8	7.8
Application space:	m ²	30-50	30-60	40-70
Temperature and humidity operating range	°C	5-35°C	5-35°C	5-35°C
	%	30-90%	30-90%	30-90%
Dimensions	mm	452	452	452
	mm	588	588	588
	mm	950	950	950
Net weight:	Kg	52	52	52
Gross weight:	Kg	55	55	55

2009V.1.0



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com