



# **PD-SSM SERIES**

## **DELUXE STAINLESS STEEL DEHUMIDIFIERS**



**Stainless Steel Casing**

**Powerful Dehumidification**

**With 10L / 16L / 20L Daily Moisture Removal**

**Intelligent Water-Level Sensor**

**By Pass Defrost**



## STANDARD SPECIFICATIONS

## PD-SSM-A SERIES

Model			PD20-SSM-A	PD30-SSM-A	PD40-SSM-A
Air Volume	m <sup>3</sup> / h		135	145	145
Humidity setting			RH40% ~ RH80%		
Applicable temperature range			5°C ~ 35°C (AUTO DEFROST)		
Moisture removal @ 30°C RH80%	L / Day		20.0	30.0	40.0
Water Tank Capacity	L		9.0	9.0	9.0
Power supply	V / Ph / Hz		220 - 240 / 1 / 50		
Running Current	A		2.6	2.7	2.7
Noise Level	dB (A)		47	45	47
Power consumption	W		480	560	580
Refrigerant			R407C		
Defrost Control			BY PASS		
Dimensions	H	mm	540	540	540
	W	mm	400	400	400
	D	mm	310	310	310
Net weight	kg		20.0	22.0	23.0

09 V.1.0


**Sonkor International Limited**
**Head Office**

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

**WEBSITE: www.sonkor.com**
**Branch Office, Spain**

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

**Branch Office, China**

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com