



PD-SSM SERIES

DELUXE STAINLESS STEEL DEHUMIDIFIERS



Stainless Steel Casing

Powerful Dehumidification

With 10L / 16L / 20L Daily Moisture Removal

Intelligent Water-Level Sensor

By Pass Defrost



STANDARD SPECIFICATIONS

PD-SSM-B SERIES

Model			PD20-SSM-B	PD30-SSM-B	PD40-SSM-B
Air Volume	m ³ / h		135	145	145
Humidity setting		RH40% ~ RH80%			
Applicable temperature range		5°C ~ 35°C (AUTO DEFROST)			
Moisture removal @ 30°C RH80%	L / Day	20.0	30.0	40.0	
Water Tank Capacity	L	9.0	9.0	9.0	
Power supply	V / Ph / Hz	110 - 120 / 1 / 60			
Running Current	A	2.6	2.7	2.7	
Noise Level	dB (A)	47	45	47	
Power consumption	W	480	560	580	
Refrigerant		R407C			
Defrost Control		BY PASS			
Dimensions	H	mm	540	540	540
	W	mm	400	400	400
	D	mm	310	310	310
Net weight	kg	20.0	22.0	23.0	

09 V.1.0


Sonkor International Limited
Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel: +852 26488887 Fax: +852 26366608 E-mail: sonkor@sonkor.com

WEBSITE: www.sonkor.com
Branch Office, Spain

AV. Juan Pablo II N°25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail: felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com