



R410A, R22

PAM-S(P)MC SERIES

DELUXE ALUMINIUM MOBILE AIR CONDITIONERS



High EER and COP ratings

Remote Control Handset

Auto Restart Memory

24-Hour Timer Setting

Soft Touch Control Panel

Elegant and refined LED Display

Powerful Cooling and Heating

Black LCD Handset (Optional)

Stylish and Modern Outlook and Innovative Design Concept



MOBILE AIR CONDITIONERS

STANDARD SPECIFICATIONS

PAM-S(P)MC SERIES R22

Model			PAM09-S(P)MC	PAM12-S(P)MC
Nominal Cooling Capacity	btu / h		9,000	12,000
	kW		2.64	3.52
Nominal Heating Capacity	btu / h		10000	13600
	kW		2.93	4.00
EER	btu / h.W		8.91	8.57
Dehumidification Capacity	L / h		1.33	2.08
Electrical Insulation Protection Class			Class I	Class I
Rated Input Current	Cooling	A	9.0	12.4
	Heating		10.4	13.6
Start Current		A	40.0	49.0
Rated Input	Cooling	kW	1.01	1.40
	Heating (H/L)		1.15	1.55
Power Supply		V / Ph / Hz	115 / 1 / 60	
Control			Electronic	
Compressor			Rotary	
Air Flow		m ³ / h	450	450
Noise Level		dB (A)	57	58
High Pressure		Mpa	2.1	2.2
Low Pressure		Mpa	0.8	0.8
Dimensions	H	mm	790	790
	W	mm	476	476
	D	mm	358	358
Packing Size	H	mm	845	845
	W	mm	540	540
	D	mm	417	417
Net Weight		kg	35.0	35.0

Remark: All above data is based on the ANSI/ASHRAE Standard 128-2001 USA Standard

09 V.1.0

All capacities are based on: cooling: 95°F RH60% (DBT95°F,WBT83°F)
 heating: 20°C RH37% (DBT20°C,WBT12°C)



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com