



R410A, R22

PAM-S(P)MD SERIES

**DELUXE STAINLESS STEEL
MOBILE AIR CONDITIONERS**



High EER and COP ratings

Black LCD Remote Control

Auto Restart Memory

24-Hour Timer Setting

Soft Touch Control Panel

Elegant and refined LED Display

Powerful Cooling and Heating

Castors Attached For Easy 360° Movement

Stylish and Modern Outlook and Innovative Design Concept



MOBILE AIR CONDITIONERS

STANDARD SPECIFICATIONS

PAM-S(P)MD SERIES R22

Model			PAM09-S(P)MD	PAM12-S(P)MD
Nominal Cooling Capacity	btu / h		9,000	12,000
	kW		2.64	3.52
Nominal Heating Capacity	btu / h		10000	13600
	kW		2.93	4.00
EER	btu / h.W		8.91	8.57
Dehumidification Capacity	L / h		1.33	2.08
Electrical Insulation Protection Class			Class I	Class I
Rated Input Current	Cooling	A	9.0	12.4
	Heating		10.4	13.6
Start Current		A	40.0	49.0
Rated Input	Cooling	kW	1.01	1.40
	Heating (H/L)		1.15	1.55
Power Supply	V / Ph / Hz		115 / 1 / 60	
Control			Electronic	
Compressor			Rotary	
Air Flow	m ³ / h		450	450
Noise Level	dB (A)		57	58
High Pressure	Mpa		2.1	2.2
Low Pressure	Mpa		0.8	0.8
Dimensions	H	mm	790	790
	W	mm	476	476
	D	mm	358	358
Packing Size	H	mm	845	845
	W	mm	540	540
	D	mm	417	417
Net Weight	kg		35.0	35.0

Remark: All above data is based on the ANSI/ASHRAE Standard 128-2001 USA Standard

09 V.1.0

All capacities are based on:
 cooling: 95°F RH60% (DBT95°F, WBT83°F)
 heating: 20°C RH37% (DBT20°C, WBT12°C)



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com