



# PDHI SERIES

## STANDARD DEHUMIDIFIERS



**Modern Hi-Tech design**

**Capacity : 30, 40 & 60 L/day**

**Powerful & Efficient dehumidifying**

**Auto continuous drainage**

**Defrost feature**

**Rotary compressor**

**360 all direction movement**



## STANDARD SPECIFICATIONS

## PDHI-A SERIES

Model			PDHI-30-A	PDHI-40-A	PDHI-60-A
Air Volume	m <sup>3</sup> / h		180	180	280
Humidity setting			RH40% ~ RH80%		
Applicable temperature range			5°C ~ 35°C		
Moisture removal @ 30°C 80%RH	L / Day		30.0	40.0	60.0
Power supply	V / Ph / Hz		230 / 1 / 50		
Running Current	A		2.3	2.6	4.0
Noise Level	dB (A)		50	50	60
Power consumption	W		500	550	980
Refrigerant			R407C		
Defrost Control			Fan Type		
Dimensions	H	mm	702	710	880
	W	mm	410	410	460
	D	mm	275	250	420
Net weight	kg		20.5	21.0	33.0

09 V.1.0


**Sonkor International Limited**
**Head Office**

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

**WEBSITE: www.sonkor.com**
**Branch Office, Spain**

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

**Branch Office, China**

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com