



R410A, R22

PAM-01(P)MA SERIES

MOBILE AIR CONDITIONERS



REMOTE CONTROL HANDSET OPERATION

MANUAL CONTROL PANEL

ELEGANT BLUE LIGHT LED DISPLAY

POWERFUL COOLING AND HEATING FUNCTIONS

BLACK LCD HANDSET (OPTIONAL)



MOBILE AIR CONDITIONERS

PAM-01(P)MA-B SERIES R22

SPECIFICATIONS

Model			PAM9-01(P)MA-B	PAM12-01(P)MA-B
Nominal Cooling Capacity	btu / h		9,000	12,000
	kW		2.64	3.52
Nominal Heating Capacity	btu / h		10,000	13,600
	kW		2.93	4.00
EER	btu / h.W		8.91	8.57
Dehumidification Capacity	L / h		1.33	2.08
Electrical Insulation Protection Class			Class I	Class I
Rated Input Current	Cooling	A	9.0	12.4
	Heating		10.4	13.6
Start Current		A	40.0	49.0
Rated Input	Cooling	kW	1.01	1.40
	Heating (H/L)		1.15	1.55
Power Supply	V / Ph / Hz		115 / 1 / 60	
Control			Electronic	
Compressor			Rotary	
Air Flow	m ³ / h		420	450
Noise Level	dB (A)		55	56
High Pressure	Mpa		2.1	2.2
Low Pressure	Mpa		0.8	0.8
Dimensions	H	mm	840	840
	W	mm	476	476
	D	mm	358	358
Net Weight	kg		31.5	32.5

Remark: All above data is based on the ANSI/ASHRAE Standard 128-2001 USA Standard

09 V.1.0

All capacities are based on:
 cooling: 95°F RH60% (DBT95°F,WBT83°F)
 heating: 20°C RH37% (DBT20°C,WBT12°C)



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com