



R410A, R22

PAM-01(P)MR-AL SERIES

MOBILE AIR CONDITIONERS



REMOTE CONTROL HANDSET OPERATION

MANUAL CONTROL PANEL

ELEGANT BLUE LIGHT LED DISPLAY

POWERFUL COOLING AND HEATING FUNCTIONS

BLACK LCD HANDSET (OPTIONAL)



MOBILE AIR CONDITIONERS

STANDARD SPECIFICATIONS

PAM-01(P)MR-A-AL SERIES R410A

Model			PAM10-01(P)MR-A-AL	PAM12-01(P)MR-A-AL	PAM14-01(P)MR-A-AL
Nominal Cooling Capacity	btu / h		10,000	11,500	13,500
	kW		3.00	3.40	4.00
Nominal Heating Capacity	btu / h		10,000	13,000	13,500
	kW		3.00	3.40	4.00
EER	kW / kW		2.62	2.62	2.62
	Energy Class		A Class	A Class	A Class
COP	kW / kW		2.85	2.66	2.66
	Energy Class		A Class	A Class	A Class
Dehumidification Capacity	L / h		1.20	1.92	1.92
Electrical Insulation Protection Class			Class I		
Rated Input Current	Cooling	A	5.20	5.80	6.80
	Heating		4.80	5.60	6.70
Start Current		A	20.0	22.0	28.0
Rated Input	Cooling	kW	1.145	1.30	1.525
	Heating (H/L)		1.05	1.26	1.50
Power Supply		V / Ph / Hz	230 / 1 / 50		
Control			Electronic		
Compressor			Rotary		
Air Flow		m ³ / h	420	450	480
Noise Level		dB (A)	54	56	56
High Pressure		Mpa	2.1	2.2	2.2
Low Pressure		Mpa	0.8	0.8	0.8
Dimensions	H	mm	880	880	880
	W	mm	540	540	540
	D	mm	417	417	417
Net Weight		kg	31.5	32.5	33.5

Remark: All above data is based on the EN14511-2007-3-2007 European Energy Efficiency Rating Standard

09 V.1.0

All capacities are based on:
 cooling: 35°C RH40% (DBT35°C,WBT24°C)
 heating: 20°C RH37% (DBT20°C,WBT12°C)



Sonkor International Limited

Head Office

Office 6, 9/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, N.T., Hong Kong

Tel : +852 26488887 Fax: +852 26366608 E-mail : sonkor@sonkor.com

WEBSITE: www.sonkor.com

Branch Office, Spain

AV. Juan Pablo II Nº25 2 4L, 30008-Murcia, Spain

Tel: +34 968270885 Fax: +34 968249520

E-mail : felipe@sonkor.com

Branch Office, China

Jinxiu 19-305, Lucheng, Wenzhou, China

Tel: +86 577 88311691 Fax: +86 577 88311691

E-mail: margaret@sonkor.com